

**Model Name:** Monitored PDU  
**Model Number:** MTV-3011M-16N2




## Description

115V, 30A, 16 Outlets, Remote Current Monitoring

## Features

<b>Current Meter</b>	Digital True RMS Current Meter
<b>Power Monitor</b>	Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
<b>Protocols</b>	Http, Https, SNMP, DHCP, UDP
<b>Alarm Thresholds</b>	User-Defined Alarm Thresholds for Warning and Overload
<b>Event Alert</b>	Email, Trap, Audible Alarm
<b>Temp./Humidity</b>	Option Accessory



## Specification

### General

Output	(16) NEMA5-20/15R
Input	(1) NEMA L5-30P attached power cord, 3 meters long
Protection	(2) 15 AMP Circuit Breaker

### Communication

SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Circuit Status	(2) Red LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A



Precision: +/-2%+/-0.1AMP

## Operation

Nominal Voltage	115V
Voltage	100V~127V full range
Frequency	50/60HZ full range
Max. Output Current	30 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1245 x 44 mm
Weight	5 kg

## Regulatory Approvals

CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3  
FCC Part 15 Class A, ICES-003

