

Model Name Switched PDU
Model Number SWH-1511A-08N1



Description

115V, 15A, 8 Outlets, Remote Current Monitoring, Remote Power Switch

Features

Current Meter	Digital True RMS Current Meter
Power Monitor	Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols	Http, Https, SNMP, DHCP, UDP
Outlet Control	Individual Outlet Control
Power Delay	Power On/Off Sequence can be Defined
Alarm Thresholds	User-Defined Alarm Thresholds for Warning and Overload
Event Alert	Email, Trap, Audible Alarm



Specification

General

Output	(8) NEMA 5-15/20R * (8) NEMA 5-15R for PSE certification
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to NEMA 5-15P Power Cord 3 Meters long
Protection	(1) 15 AMP Circuit Breaker

Communication

SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%/+/-0.1AMP

Operation

Nominal Voltage	115V
Voltage	100V~127V full range
Frequency	50/60HZ full range
Max. Output Current	15 Amp (UL derated 12 Amp)
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	90 x 432 x 44 mm
Weight	2 kg

Regulatory Approvals

UL 60950-1, UL Listed, CSA, cUL Listed,
CB by UL
CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
FCC Part 15 Class A, ICES-003
PSE

