

Model Name Switched PDU
Model Number SWV-2011B-16N1

Input



Description

115V, 20A, 16 Outlets, Remote Current Monitoring, Remote Power Switch

Features

- Current Meter** Digital True RMS Current Meter
- Power Monitor** Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols** Http, Https, SNMP, DHCP, UDP
- Outlet Control** Individual Outlet Control
- Power Delay** Power On/Off Sequence can be Defined
- Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload
- Event Alert** Email, Trap, Audible Alarm



Specification

General

- Output** (16) NEMA 5-20/15R
- Input** (1) IEC320 C20 Inlet;
Enclosed IEC320 C19 to NEMA 5-20P Power Cord
3 Meters long
- Protection** (1) 20 AMP Circuit Breaker

Communication

- SSL Indication** (1) Yellow LED
- DHCP Indication** (1) Green LED
- Output Status** (16) Green LED
- Network** (1) RJ45 for Ethernet



Current Meter 3 Digits Seven Segments for True RMS Meter
Range: 0A ~ 20 A
Resolution: 0.1A
Precision: +/-2%+/-0.1AMP

Operation

Nominal Voltage 115V
Voltage 100V~127V full range
Frequency 50/60HZ full range
Max. Output Current 20 Amp (UL derated 16 Amp)
Temperature 0 ~ 40 Celsius degree
Humidity 0% ~ 90%
Size 56 x 1245 x 44 mm
Weight 4 kg

Regulatory Approvals

UL 60950-1, UL Listed, CSA, cUL Listed,
CB by UL
CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN
61000-3-3
FCC Part 15 Class A, ICES-003

