

Model Name Switched PDU
Model Number SWV-3011M-24N3

Input



Description

115V, 30A, 24 Outlets, Remote Current Monitoring, Remote Power Switch

Features

- Current Meter** Digital True RMS Current Meter
- Power Monitor** Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols** Http, Https, SNMP, DHCP, UDP
- Outlet Control** Individual Outlet Control
- Power Delay** Power On/Off Sequence can be Defined
- Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload
- Temp./Humidity** Option Accessory
- Event Alert** Email, Trap, Audible Alarm



Specification

General

- Output** (24) NEMA5-20/15R
- Input** (1) L5-30P attached power cord, 3 meters long
- Protection** (3) 20 AMP Circuit Breaker

Communication

- SSL Indication** (1) Yellow LED
- DHCP Indication** (1) Green LED
- Circuit Status** (3) Red LED
- Output Status** (24) Green LED



Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%+/-0.1AMP

Operation

Nominal Voltage	115V
Voltage	100V~127V full range
Frequency	50/60HZ full range
Max. Output Current	30 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1778 x 44 mm
Weight	6 kg

Regulatory Approvals

CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
FCC Part 15 Class A, ICES-003

